

AMENDMENTS TO THE CLAIMS

Claim 1 (currently amended). A mass transit vehicle window installation assembly for simplifying and accelerating the installation of window assemblies in vehicle window apertures, the assembly comprising:

a retainer configured to connect between a window assembly frame and a vehicle wall panel having a window aperture shaped to receive the window assembly, where the window assembly frame ~~[is configured to support a window assembly pane and]~~ has a planform shape that generally complements that of the window aperture;

the retainer being additionally configured to space such a window assembly frame from an inner peripheral surface of a complementary window aperture; and

Q1 the retainer being additionally configured to be supported on one of a window frame and a complementary window aperture in a position to center the window assembly as the window assembly is inserted into the aperture.

Claim 2 (original). A mass transit vehicle window installation assembly as defined in claim 1 in which the retainer is additionally configured to retain a window frame within a complementary window aperture.

Claim 3 (original). A mass transit vehicle window installation assembly for simplifying and accelerating the installation of window assemblies in vehicle window apertures, the assembly comprising:

a plurality of window assembly retainers securable at spaced locations around and between a window frame and a window aperture;

each retainer of the plurality of retainers being configured to connect between a window assembly frame and a vehicle wall panel having a window aperture shaped to receive the window assembly, where the window assembly frame has a planform shape that generally complements that of the window aperture;

the plurality of retainers being additionally configured to space such a window frame from an inner peripheral surface of a complementary window aperture;

each retainer of the plurality of retainers being additionally configured to be supported on one of a window frame and a complementary window aperture in respective positions and to cooperatively center the window assembly as the window assembly is inserted into the aperture.

Claim 4 (original). A mass transit vehicle window installation assembly as defined in claim 3 in which each retainer is additionally configured to retain the window frame within a complementary window aperture.

Q1 Claim 5 (original). A mass transit vehicle window installation assembly as defined in claim 4 in which each retainer includes a spring clip configured to be fixed to a window frame and to snap outward into engagement with a recessed window aperture detent formed into an inside peripheral wall of a window aperture that is to receive the window frame.

Claim 6 (original). A mass transit vehicle window installation assembly as defined in claim 3 in which at least one retainer of the plurality of retainers is configured to be fixed to an outer peripheral wall of the window frame.

Claim 7 (original). A mass transit vehicle window installation assembly as defined in claim 6 in which:

at least one retainer includes a spring clip that includes an elongated resilient spring arm biased outwardly from a mounting base of the spring clip that attaches to the outer peripheral wall of the window frame; and

the spring arm is configured to bend inwardly when contacting a front edge of a window aperture that the window assembly is being inserted into and then to spring back outward when the window assembly is fully inserted and an outer distal end of the spring arm passes over a recess defining the aperture detent, the distal end of the spring arm engaging the aperture detent once the spring arm has sprung back outward.

Claim 8 (original). A mass transit vehicle window installation assembly as defined in claim 7 in which the spring arm of at least one retainer comprises an elongated strip of spring steel.

Q' Claim 9 (currently amended). A mass transit vehicle window installation assembly as defined in claim 7 in which the distal end of the spring arm of at least one retainer includes a centering surface configured to engage an inner peripheral surface of a window aperture ~~[to space the window frame a predetermined desired distance from an inner peripheral surface of a window aperture that the window assembly is inserted into, and to prevent the spring arm from springing too far outward and causing the distal end of the spring arm to pass and miss engagement with an aperture detent formed in the inner peripheral wall of the window aperture].~~

Claim 10 (original). A mass transit vehicle window installation assembly as defined in claim 9 in which:

at least one retainer includes a spring arm that extends from a mounting base of the retainer in a direction that, when the retainer is attached to an outer peripheral wall of a window frame, is generally opposite the direction of window assembly insertion; and

the distal end of the spring arm includes an S-bend forming a detent surface that abuts a recessed window aperture detent formed into an inside peripheral wall of a window aperture that is to receive the window frame; and

the distal end also includes an adjacent outer tab that includes the centering surface for engaging an inner peripheral surface of the receiving window aperture.

Claim 11 (original). A mass transit vehicle window installation assembly as defined in claim 9 in which at least one retainer includes a spring arm that extends from a mounting base of the retainer in a direction that, when the retainer is attached to an outer peripheral wall of a window frame, is generally the same as the direction of window assembly insertion, and the distal end is configured to hook over a back edge of the receiving window aperture to secure the window assembly against extraction opposite the direction of window assembly insertion.

Claim 12 (original). A mass transit vehicle window installation assembly as defined in claim 4 in which at least one retainer comprises a spring clip including:

a mounting base configured to support the retainer on a window assembly frame;
and

a spring arm extending from the mounting base and configured to bend inward toward the mounting base when a window assembly frame that the retainer is supported on is inserted into a receiving window aperture and the spring arm engages a front edge of the aperture, the spring clip being further configured to continuously bias a distal end of the spring arm outward against an inner peripheral surface of the aperture, the distal end of the spring arm being configured to engage the inner peripheral surface of the aperture in such a way as to provide an interference fit for the window assembly within the receiving window aperture.

Q1

Claim 13 (original). A mass transit vehicle window installation assembly as defined in claim 12 in which:

at least one retainer comprises a spring clip having a spring arm that, when the retainer is supported on a window frame, extends from a mounting base of the retainer in a direction generally opposite the direction of window assembly insertion; and

the distal end of the spring arm includes a saw tooth edge configured to dig into an inner peripheral surface of the receiving window aperture to a depth sufficient to secure the window assembly against extraction from the window aperture opposite the direction of window assembly insertion.

Claim 14 (original). A mass transit vehicle window installation assembly as defined in either claim 1 or 3 in which:

the retainer includes a trim strip ring that approximates the outer planform shape of a window aperture and a complementary window assembly frame configured to be installed in that window aperture;

the trim strip ring is configured to engage respective back surfaces of the window assembly frame and a wall panel that the aperture is formed in and to cover a gap formed between a peripheral outer surface of the window frame and a peripheral inner surface of the window aperture when the window frame is installed in a window aperture in the wall panel.

Claim 15 (original). A mass transit vehicle window installation assembly as defined in claim 14 in which the trim strip ring includes an elongated stem configured to be inserted in a gap formed between a peripheral outer surface of a window assembly frame and peripheral inner surface of a window aperture receiving the window assembly frame.

R1
Claim 16 (original). A mass transit vehicle window installation assembly as defined in claim 14 in which the trim strip ring includes an elongated seal ring configured to prevent moisture and drafts of air from passing through a gap formed between a peripheral outer surface of a window assembly frame and peripheral inner surface of a window aperture receiving the window assembly frame.

Claim 17 (original). A mass transit vehicle window installation assembly as defined in either claim 1 or claim 3 in which:

the vehicle window installation assembly includes a window assembly frame having a front flange that extends outward from a main portion of the frame in a position disposed against a front surface of a wall panel that the window assembly is installed in;

the front flange covers the gap between the window frame and the inner peripheral wall of a window aperture that the window assembly is installed in; and

an elongated rubber seal ring is connected around and along a back surface of the front flange in a position to seal against the front surface of the wall panel.

Claim 18 (original). A mass transit vehicle window installation assembly as defined in claim 7 in which the mounting base of the spring clip of at least one of the retainers includes a pair of radially extending diametrically opposed

attachment ears configured to engage respective opposing lateral undercuts formed along opposite sidewalls of a groove formed around and outer peripheral wall of a window frame.

Claim 19 (original). A mass transit vehicle window installation assembly as defined in claim 4 in which at least one of the retainers includes a spring clip configured to be supported on the window aperture and to engage a window assembly frame when the window assembly frame is inserted into a complementary window aperture.

R' Claim 20 (original). A mass transit vehicle window installation assembly as defined in claim 4 in which at least one retainer of the plurality of retainers includes a spring clip configured to engage opposing channel side walls of a channel formed into and around an inner peripheral wall of a receiving window aperture.

Claim 21 (original). A mass transit vehicle window installation assembly as defined in claim 20 in which the spring clip of at least one retainer includes a pair of legs that extend from a base element of the clip and are shaped to engage a pair of elongated flanges that extend inwardly from opposing channel sidewalls of a channel formed into and around an inner peripheral wall of the window aperture.

Claim 22 (original). A mass transit vehicle window installation assembly as defined in claim 21 in which the legs of the spring clip of the at least one retainer have S-shaped bends configured to allow the legs to bend inward as they are being pressed into a channel past flanges that extend inwardly from opposing channel sidewalls and then to snap back outwards into a position engaging the flanges and precluding extraction.

Claim 23 (original). A mass transit vehicle window installation assembly as defined in claim 21 in which the legs of the spring clip of the at least one

retainer are long enough to prevent the clip from falling into the channel or track without engaging the flanges.

Claim 24 (original). A mass transit vehicle window installation assembly as defined in claim 21 in which:

Q1
could
the clip includes a resilient spring arm that extends diagonally from the base element of the clip in a direction generally opposite the direction intended for insertion of a window assembly frame;

the spring arm is configured to bend outwardly toward the inner peripheral wall of a window aperture that the clip is installed in when contacting a front edge of a window assembly frame that is being inserted into the window aperture.

Claim 25 (original). A mass transit vehicle window installation assembly as defined in claim 24 in which a plurality of the spring clips are spaced around the inner peripheral wall of the window aperture so that a collective inward bias of the spring arms of the spring clips centers the window assembly in the window aperture upon insertion.

Claims 26-39 (withdrawn).
